





Cable Entry

INLINE
 Cable Entry

RIGHT / LEFT
 Cable Entry

REAR
 Cable Entry

END CAP



Mounting Profile Information

Accessory: Marineflex Profile

ITEM NO. 42149 - MF-PROFILE-1M


Accessory: Marineflex Clip

ITEM NO. 42150 - MF-CLIP



Driver Configuration Table

MARINEFLEX-SIDE-TW 13W/M			
BC Code	DRIVER (Non-Dim)	SPECIFICATION	MARINEFLEX LENGTH
15210	ORLRPV2435	LED Driver, DC24V, 35W	Up to 2.5M
15214	ORLRPV2460	LED Driver, DC24V, 60W	Up to 4.5M
15199	ORLRPV24100	LED Driver, DC24V, 100W	Up to 7.5M
15203	ORLRPV24150	LED Driver, DC24V, 150W	Up to 10M
	INTERFACE		
34998	ORLDALIIF-12-24-36V-TW-RGBW-DT8	DALI DT8 TW RGBW INTERFACE	Up to 10M

Length Matrix

The MARINEFLEX-SIDE-TW can be cut every 71.4mm. The below table gives information on the overall length, obtained by adding the total cable entry length and end mould, to all the available cut lengths up to 10M. **If you require lengths beyond the standard 10M then please contact sales@orlight.com.**

Note: Allow for a tolerance of +/- 0.3mm on cut points.

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
1	71.4	91.1	77.4	77.4
2	142.8	162.5	148.8	148.8
3	214.2	233.9	220.2	220.2
4	285.6	305.3	291.6	291.6
5	357.0	376.7	363.0	363.0
6	428.4	448.1	434.4	434.4
7	499.8	519.5	505.8	505.8
8	571.2	590.9	577.2	577.2
9	642.6	662.3	648.6	648.6
10	714.0	733.7	720.0	720.0
11	785.4	805.1	791.4	791.4
12	856.8	876.5	862.8	862.8
13	928.2	947.9	934.2	934.2
14	999.6	1019.3	1005.6	1005.6
15	1071.0	1090.7	1077.0	1077.0
16	1142.4	1162.1	1148.4	1148.4
17	1213.8	1233.5	1219.8	1219.8
18	1285.2	1304.9	1291.2	1291.2
19	1356.6	1376.3	1362.6	1362.6
20	1428.0	1447.7	1434.0	1434.0
21	1499.4	1519.1	1505.4	1505.4
22	1570.8	1590.5	1576.8	1576.8
23	1642.2	1661.9	1648.2	1648.2
24	1713.6	1733.3	1719.6	1719.6
25	1785.0	1804.7	1791.0	1791.0
26	1856.4	1876.1	1862.4	1862.4
27	1927.8	1947.5	1933.8	1933.8
28	1999.2	2018.9	2005.2	2005.2
29	2070.6	2090.3	2076.6	2076.6
30	2142.0	2161.7	2148.0	2148.0
31	2213.4	2233.1	2219.4	2219.4
32	2284.8	2304.5	2290.8	2290.8
33	2356.2	2375.9	2362.2	2362.2
34	2427.6	2447.3	2433.6	2433.6
35	2499.0	2518.7	2505.0	2505.0
36	2570.4	2590.1	2576.4	2576.4
37	2641.8	2661.5	2647.8	2647.8
38	2713.2	2732.9	2719.2	2719.2
39	2784.6	2804.3	2790.6	2790.6
40	2856.0	2875.7	2862.0	2862.0
41	2927.4	2947.1	2933.4	2933.4
42	2998.8	3018.5	3004.8	3004.8
43	3070.2	3089.9	3076.2	3076.2
44	3141.6	3161.3	3147.6	3147.6
45	3213.0	3232.7	3219.0	3219.0

Length Matrix

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
46	3284.4	3304.1	3290.4	3290.4
47	3355.8	3375.5	3361.8	3361.8
48	3427.2	3446.9	3433.2	3433.2
49	3498.6	3518.3	3504.6	3504.6
50	3570.0	3589.7	3576.0	3576.0
51	3641.4	3661.1	3647.4	3647.4
52	3712.8	3732.5	3718.8	3718.8
53	3784.2	3803.9	3790.2	3790.2
54	3855.6	3875.3	3861.6	3861.6
55	3927.0	3946.7	3933.0	3933.0
56	3998.4	4018.1	4004.4	4004.4
57	4069.8	4089.5	4075.8	4075.8
58	4141.2	4160.9	4147.2	4147.2
59	4212.6	4232.3	4218.6	4218.6
60	4284.0	4303.7	4290.0	4290.0
61	4355.4	4375.1	4361.4	4361.4
62	4426.8	4446.5	4432.8	4432.8
63	4498.2	4517.9	4504.2	4504.2
64	4569.6	4589.3	4575.6	4575.6
65	4641.0	4660.7	4647.0	4647.0
66	4712.4	4732.1	4718.4	4718.4
67	4783.8	4803.5	4789.8	4789.8
68	4855.2	4874.9	4861.2	4861.2
69	4926.6	4946.3	4932.6	4932.6
70	4998.0	5017.7	5004.0	5004.0
71	5069.4	5089.1	5075.4	5075.4
72	5140.8	5160.5	5146.8	5146.8
73	5212.2	5231.9	5218.2	5218.2
74	5283.6	5303.3	5289.6	5289.6
75	5355.0	5374.7	5361.0	5361.0
76	5426.4	5446.1	5432.4	5432.4
77	5497.8	5517.5	5503.8	5503.8
78	5569.2	5588.9	5575.2	5575.2
79	5640.6	5660.3	5646.6	5646.6
80	5712.0	5731.7	5718.0	5718.0
81	5783.4	5803.1	5789.4	5789.4
82	5854.8	5874.5	5860.8	5860.8
83	5926.2	5945.9	5932.2	5932.2
84	5997.6	6017.3	6003.6	6003.6
85	6069.0	6088.7	6075.0	6075.0
86	6140.4	6160.1	6146.4	6146.4
87	6211.8	6231.5	6217.8	6217.8
88	6283.2	6302.9	6289.2	6289.2
89	6354.6	6374.3	6360.6	6360.6
90	6426.0	6445.7	6432.0	6432.0
91	6497.4	6517.1	6503.4	6503.4
92	6568.8	6588.5	6574.8	6574.8
93	6640.2	6659.9	6646.2	6646.2
94	6711.6	6731.3	6717.6	6717.6

Length Matrix

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
95	6783.0	6802.7	6789.0	6789.0
96	6854.4	6874.1	6860.4	6860.4
97	6925.8	6945.5	6931.8	6931.8
98	6997.2	7016.9	7003.2	7003.2
99	7068.6	7088.3	7074.6	7074.6
100	7140.0	7159.7	7146.0	7146.0
101	7211.4	7231.1	7217.4	7217.4
102	7282.8	7302.5	7288.8	7288.8
103	7354.2	7373.9	7360.2	7360.2
104	7425.6	7445.3	7431.6	7431.6
105	7497.0	7516.7	7503.0	7503.0
106	7568.4	7588.1	7574.4	7574.4
107	7639.8	7659.5	7645.8	7645.8
108	7711.2	7730.9	7717.2	7717.2
109	7782.6	7802.3	7788.6	7788.6
110	7854.0	7873.7	7860.0	7860.0
111	7925.4	7945.1	7931.4	7931.4
112	7996.8	8016.5	8002.8	8002.8
113	8068.2	8087.9	8074.2	8074.2
114	8139.6	8159.3	8145.6	8145.6
115	8211.0	8230.7	8217.0	8217.0
116	8282.4	8302.1	8288.4	8288.4
117	8353.8	8373.5	8359.8	8359.8
118	8425.2	8444.9	8431.2	8431.2
119	8496.6	8516.3	8502.6	8502.6
120	8568.0	8587.7	8574.0	8574.0
121	8639.4	8659.1	8645.4	8645.4
122	8710.8	8730.5	8716.8	8716.8
123	8782.2	8801.9	8788.2	8788.2
124	8853.6	8873.3	8859.6	8859.6
125	8925.0	8944.7	8931.0	8931.0
126	8996.4	9016.1	9002.4	9002.4
127	9067.8	9087.5	9073.8	9073.8
128	9139.2	9158.9	9145.2	9145.2
129	9210.6	9230.3	9216.6	9216.6
130	9282.0	9301.7	9288.0	9288.0
131	9353.4	9373.1	9359.4	9359.4
132	9424.8	9444.5	9430.8	9430.8
133	9496.2	9515.9	9502.2	9502.2
134	9567.6	9587.3	9573.6	9573.6
135	9639.0	9658.7	9645.0	9645.0
136	9710.4	9730.1	9716.4	9716.4
137	9781.8	9801.5	9787.8	9787.8
138	9853.2	9872.9	9859.2	9859.2
139	9924.6	9944.3	9930.6	9930.6
140	9996.0	10015.7	10002.0	10002.0

NOTE: The max length power from one side is 10 meters. The overall lengths are including Ends, please also allow for +/- 0.3mm Tolerance on overall length. Products are injection moulded by machine that is man operated therefore please allow a tolerance of 5mm.