





Cable Entry

INLINE
 Cable Entry

RIGHT / LEFT
 Cable Entry

REAR
 Cable Entry

END CAP



Mounting Profile Information

Accessory: Marineflex Profile

ITEM NO. 42149 - MF-PROFILE-1M


Accessory: Marineflex Clip

ITEM NO. 42150 - MF-CLIP



Driver Configuration Table

MARINEFLEX-TOP 14.4W/M			
BC Code	DRIVER (Non-Dim)	SPECIFICATION	MARINEFLEX LENGTH
15210	ORLRPV2435	LED Driver, DC24V, 35W	Up to 2.3M
15214	ORLRPV2460	LED Driver, DC24V, 60W	Up to 4M
15199	ORLRPV24100	LED Driver, DC24V, 100W	Up to 6.8M
15203	ORLRPV24150	LED Driver, DC24V, 150W	Up to 10M
	DRIVER (Mains Dim)		
15221	ORLRPV25-24MD	LED 25W Mains Dimmable Driver 24V	Up to 1.5M
15250	ORLRPV50-24MD	LED 50W Mains Dimmable Driver 24V	Up to 3.3M
15169	ORLRPV100-24MD	LED 100W Mains Dimmable Driver 24V	Up to 6.8M
15193	ORLRPV150-24MD	LED 150W Mains Dimmable Driver 24V	Up to 10M
	INTERFACE		
15357	ORLRPV-INTERFACE-MINI	1-10V INTERFACE	Up to 10M
14054	ORLDALIINTERFACE-12/24/36V	DALI INTERFACE	Up to 10M

Length Matrix

The MARINEFLEX-TOP can be cut every 50mm. The below table gives information on the overall length, obtained by adding the total cable entry length and end mould, to all the available cut lengths up to 10M. **If you require lengths beyond the standard 10M then please contact sales@orlight.com.**

Note: Allow for a tolerance of +/- 0.3mm on cut points.

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
1	50.0	69.7	56.0	56.0
2	100.0	119.7	106.0	106.0
3	150.0	169.7	156.0	156.0
4	200.0	219.7	206.0	206.0
5	250.0	269.7	256.0	256.0
6	300.0	319.7	306.0	306.0
7	350.0	369.7	356.0	356.0
8	400.0	419.7	406.0	406.0
9	450.0	469.7	456.0	456.0
10	500.0	519.7	506.0	506.0
11	550.0	569.7	556.0	556.0
12	600.0	619.7	606.0	606.0
13	650.0	669.7	656.0	656.0
14	700.0	719.7	706.0	706.0
15	750.0	769.7	756.0	756.0
16	800.0	819.7	806.0	806.0
17	850.0	869.7	856.0	856.0
18	900.0	919.7	906.0	906.0
19	950.0	969.7	956.0	956.0
20	1000.0	1019.7	1006.0	1006.0
21	1050.0	1069.7	1056.0	1056.0
22	1100.0	1119.7	1106.0	1106.0
23	1150.0	1169.7	1156.0	1156.0
24	1200.0	1219.7	1206.0	1206.0
25	1250.0	1269.7	1256.0	1256.0
26	1300.0	1319.7	1306.0	1306.0
27	1350.0	1369.7	1356.0	1356.0
28	1400.0	1419.7	1406.0	1406.0
29	1450.0	1469.7	1456.0	1456.0
30	1500.0	1519.7	1506.0	1506.0
31	1550.0	1569.7	1556.0	1556.0
32	1600.0	1619.7	1606.0	1606.0
33	1650.0	1669.7	1656.0	1656.0
34	1700.0	1719.7	1706.0	1706.0
35	1750.0	1769.7	1756.0	1756.0
36	1800.0	1819.7	1806.0	1806.0
37	1850.0	1869.7	1856.0	1856.0
38	1900.0	1919.7	1906.0	1906.0
39	1950.0	1969.7	1956.0	1956.0
40	2000.0	2019.7	2006.0	2006.0
41	2050.0	2069.7	2056.0	2056.0
42	2100.0	2119.7	2106.0	2106.0
43	2150.0	2169.7	2156.0	2156.0
44	2200.0	2219.7	2206.0	2206.0
45	2250.0	2269.7	2256.0	2256.0

Length Matrix

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
46	2300.0	2319.7	2306.0	2306.0
47	2350.0	2369.7	2356.0	2356.0
48	2400.0	2419.7	2406.0	2406.0
49	2450.0	2469.7	2456.0	2456.0
50	2500.0	2519.7	2506.0	2506.0
51	2550.0	2569.7	2556.0	2556.0
52	2600.0	2619.7	2606.0	2606.0
53	2650.0	2669.7	2656.0	2656.0
54	2700.0	2719.7	2706.0	2706.0
55	2750.0	2769.7	2756.0	2756.0
56	2800.0	2819.7	2806.0	2806.0
57	2850.0	2869.7	2856.0	2856.0
58	2900.0	2919.7	2906.0	2906.0
59	2950.0	2969.7	2956.0	2956.0
60	3000.0	3019.7	3006.0	3006.0
61	3050.0	3069.7	3056.0	3056.0
62	3100.0	3119.7	3106.0	3106.0
63	3150.0	3169.7	3156.0	3156.0
64	3200.0	3219.7	3206.0	3206.0
65	3250.0	3269.7	3256.0	3256.0
66	3300.0	3319.7	3306.0	3306.0
67	3350.0	3369.7	3356.0	3356.0
68	3400.0	3419.7	3406.0	3406.0
69	3450.0	3469.7	3456.0	3456.0
70	3500.0	3519.7	3506.0	3506.0
71	3550.0	3569.7	3556.0	3556.0
72	3600.0	3619.7	3606.0	3606.0
73	3650.0	3669.7	3656.0	3656.0
74	3700.0	3719.7	3706.0	3706.0
75	3750.0	3769.7	3756.0	3756.0
76	3800.0	3819.7	3806.0	3806.0
77	3850.0	3869.7	3856.0	3856.0
78	3900.0	3919.7	3906.0	3906.0
79	3950.0	3969.7	3956.0	3956.0
80	4000.0	4019.7	4006.0	4006.0
81	4050.0	4069.7	4056.0	4056.0
82	4100.0	4119.7	4106.0	4106.0
83	4150.0	4169.7	4156.0	4156.0
84	4200.0	4219.7	4206.0	4206.0
85	4250.0	4269.7	4256.0	4256.0
86	4300.0	4319.7	4306.0	4306.0
87	4350.0	4369.7	4356.0	4356.0
88	4400.0	4419.7	4406.0	4406.0
89	4450.0	4469.7	4456.0	4456.0
90	4500.0	4519.7	4506.0	4506.0
91	4550.0	4569.7	4556.0	4556.0
92	4600.0	4619.7	4606.0	4606.0
93	4650.0	4669.7	4656.0	4656.0
94	4700.0	4719.7	4706.0	4706.0

Length Matrix

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
95	4750.0	4769.7	4756.0	4756.0
96	4800.0	4819.7	4806.0	4806.0
97	4850.0	4869.7	4856.0	4856.0
98	4900.0	4919.7	4906.0	4906.0
99	4950.0	4969.7	4956.0	4956.0
100	5000.0	5019.7	5006.0	5006.0
101	5050.0	5069.7	5056.0	5056.0
102	5100.0	5119.7	5106.0	5106.0
103	5150.0	5169.7	5156.0	5156.0
104	5200.0	5219.7	5206.0	5206.0
105	5250.0	5269.7	5256.0	5256.0
106	5300.0	5319.7	5306.0	5306.0
107	5350.0	5369.7	5356.0	5356.0
108	5400.0	5419.7	5406.0	5406.0
109	5450.0	5469.7	5456.0	5456.0
110	5500.0	5519.7	5506.0	5506.0
111	5550.0	5569.7	5556.0	5556.0
112	5600.0	5619.7	5606.0	5606.0
113	5650.0	5669.7	5656.0	5656.0
114	5700.0	5719.7	5706.0	5706.0
115	5750.0	5769.7	5756.0	5756.0
116	5800.0	5819.7	5806.0	5806.0
117	5850.0	5869.7	5856.0	5856.0
118	5900.0	5919.7	5906.0	5906.0
119	5950.0	5969.7	5956.0	5956.0
120	6000.0	6019.7	6006.0	6006.0
121	6050.0	6069.7	6056.0	6056.0
122	6100.0	6119.7	6106.0	6106.0
123	6150.0	6169.7	6156.0	6156.0
124	6200.0	6219.7	6206.0	6206.0
125	6250.0	6269.7	6256.0	6256.0
126	6300.0	6319.7	6306.0	6306.0
127	6350.0	6369.7	6356.0	6356.0
128	6400.0	6419.7	6406.0	6406.0
129	6450.0	6469.7	6456.0	6456.0
130	6500.0	6519.7	6506.0	6506.0
131	6550.0	6569.7	6556.0	6556.0
132	6600.0	6619.7	6606.0	6606.0
133	6650.0	6669.7	6656.0	6656.0
134	6700.0	6719.7	6706.0	6706.0
135	6750.0	6769.7	6756.0	6756.0
136	6800.0	6819.7	6806.0	6806.0
137	6850.0	6869.7	6856.0	6856.0
138	6900.0	6919.7	6906.0	6906.0
139	6950.0	6969.7	6956.0	6956.0
140	7000.0	7019.7	7006.0	7006.0
141	7050.0	7069.7	7056.0	7056.0
142	7100.0	7119.7	7106.0	7106.0
143	7150.0	7169.7	7156.0	7156.0

Length Matrix

Segments	Luminaire/ Cutpoints	Total Length (mm)		
		Inline+End	Left/Right+End	Rear+End
144	7200.0	7219.7	7206.0	7206.0
145	7250.0	7269.7	7256.0	7256.0
146	7300.0	7319.7	7306.0	7306.0
147	7350.0	7369.7	7356.0	7356.0
148	7400.0	7419.7	7406.0	7406.0
149	7450.0	7469.7	7456.0	7456.0
150	7500.0	7519.7	7506.0	7506.0
151	7550.0	7569.7	7556.0	7556.0
152	7600.0	7619.7	7606.0	7606.0
153	7650.0	7669.7	7656.0	7656.0
154	7700.0	7719.7	7706.0	7706.0
155	7750.0	7769.7	7756.0	7756.0
156	7800.0	7819.7	7806.0	7806.0
157	7850.0	7869.7	7856.0	7856.0
158	7900.0	7919.7	7906.0	7906.0
159	7950.0	7969.7	7956.0	7956.0
160	8000.0	8019.7	8006.0	8006.0
161	8050.0	8069.7	8056.0	8056.0
162	8100.0	8119.7	8106.0	8106.0
163	8150.0	8169.7	8156.0	8156.0
164	8200.0	8219.7	8206.0	8206.0
165	8250.0	8269.7	8256.0	8256.0
166	8300.0	8319.7	8306.0	8306.0
167	8350.0	8369.7	8356.0	8356.0
168	8400.0	8419.7	8406.0	8406.0
169	8450.0	8469.7	8456.0	8456.0
170	8500.0	8519.7	8506.0	8506.0
171	8550.0	8569.7	8556.0	8556.0
172	8600.0	8619.7	8606.0	8606.0
173	8650.0	8669.7	8656.0	8656.0
174	8700.0	8719.7	8706.0	8706.0
175	8750.0	8769.7	8756.0	8756.0
176	8800.0	8819.7	8806.0	8806.0
177	8850.0	8869.7	8856.0	8856.0
178	8900.0	8919.7	8906.0	8906.0
179	8950.0	8969.7	8956.0	8956.0
180	9000.0	9019.7	9006.0	9006.0
181	9050.0	9069.7	9056.0	9056.0
182	9100.0	9119.7	9106.0	9106.0
183	9150.0	9169.7	9156.0	9156.0
184	9200.0	9219.7	9206.0	9206.0
185	9250.0	9269.7	9256.0	9256.0
186	9300.0	9319.7	9306.0	9306.0
187	9350.0	9369.7	9356.0	9356.0
188	9400.0	9419.7	9406.0	9406.0
189	9450.0	9469.7	9456.0	9456.0
190	9500.0	9519.7	9506.0	9506.0
191	9550.0	9569.7	9556.0	9556.0
192	9600.0	9619.7	9606.0	9606.0

Length Matrix

		Total Length (mm)		
Segments	Luminaire/ Cutpoints	Inline+End	Left/Right+End	Rear+End
193	9650.0	9669.7	9656.0	9656.0
194	9700.0	9719.7	9706.0	9706.0
195	9750.0	9769.7	9756.0	9756.0
196	9800.0	9819.7	9806.0	9806.0
197	9850.0	9869.7	9856.0	9856.0
198	9900.0	9919.7	9906.0	9906.0
199	9950.0	9969.7	9956.0	9956.0
200	10000.0	10019.7	10006.0	10006.0

NOTE: The max length power from one side is 10 meters. The overall lengths are including Ends, please also allow for +/- 0.3mm Tolerance on overall length. Products are injection moulded by machine that is man operated therefore please allow a tolerance of 5mm.