

Ref:

ORLTE6024EVO4-4000K-IP65-25W-S


Item No: EVO4 – 15479-S



High output self-adhesive LED strip. The EVO4 strip is supplied per metre complete with plug and play connections. Featuring 3M adhesive backing for simple installation. It can be cut every 33mm, allowing you to tailor the strip to your exact needs. A layer of Nano coating provides an IP65 rating. CRI>90 standard ensures enhanced light quality with uncompromising standards.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	25W/M
Lumen Output	3532LM
Efficacy	141LM/W
CCT	4000K
CRI	CRI > 94
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	SMD 2835
Calculated Chip Life	L70 > 105,000HRS


ELECTRICAL

Constant Current or Voltage	CONSTANT VOLTAGE
Voltage	24V
Cable Length	300 MM

CONSTRUCTION

Installation	PLUG & PLAY
Construction	PCB & NANO COATING
Width / Depth	12 MM
Height	2 MM
IP Rating	IP65
Cut Points	33 MM
Max Cut Length	5000 MM

LIGHT DISTRIBUTION



DRIVER CONFIGURATION

CONTROL	DRIVER	CODE	MAX. LENGTH
Switched	ORLRPV2435	15210	1M
Switched	ORLRPV2460	15214	2M
Switched	ORLRPV24100	15199	4M
Switched	ORLRPV24150	15203	5M
Mains Dimmable	ORLRPV25-24MD	15221	1M
Mains Dimmable	ORLRPV50-24MD	15250	2M
Mains Dimmable	ORLRPV100-24MD	15169	4M
Mains Dimmable	ORLRPV150-24MD	15193	5M
1-10V Interface	ORLRPV-INTERFACE-MINI	15357	-
DALI	ORLDALIINTERFACE-12-24-36V	14054	-

POWER SUPPLY



ORLRPV2435
15210
24V Switched Driver



ORLRPV2460
15214
24V Switched Driver



ORLRPV24100
15199
24V Switched Driver



ORLRPV24150
15203
24V Switched Driver

ORLTE6024EVO4-4000K-IP65-25W-S

Item No: EVO4 – 15479-S

orlight®
FROM SOURCE TO SITE

MAINS DIMMABLE



ORLRPV25-24MD
15221
24V Mains Dimmable Driver



ORLRPV50-24MD
15250
24V Mains Dimmable Driver



ORLRPV100-24MD
15169
24V Mains Dimmable Driver



ORLRPV150-24MD
15193
24V Mains Dimmable Driver

1-10V/DALI INTERFACE




ORLRPV-INTERFACE-MINI
15357
Constant Voltage Interface for 1-10V dimming




ORLDALIINTERFACE-12-24-36V
14054
DALI/PUSH Dimmable Interface

COMPATIBLE DIFFUSER



ORLRPVHSEVOPL2-S-CL-2M
15348
Square Clear Diffuser



ORLRPVHSEVOPL2C-S-2M
15338
Square Corner Opal Diffuser




ORLRPVHSEVOPL2C-R-2M
15334
Round Corner Opal Diffuser




ORLRPVALUHS-TP7-2M
15322
Narrow Opal Diffuser




ORLRPVALUHS-TP30-2M
15319
Square Top Lit Opal Diffuser



ORLRPVALUHS-TL-2M
15309
Trimless Opal Diffuser



ORLRPVALUHS-TL15-2M
15307
Trimless Opal Diffuser




ORLRPVALUHS-SR-WH-2M
15304
Semi Recessed Opal Diffuser

ORLTE6024EVO4-4000K-IP65-25W-S

Item No: EVO4 – 15479-S

orlight[®]
FROM SOURCE TO SITE



ORLRPVALUHS-SR-AL-2M
15299
Semi Recessed Opal Diffuser




ORLRPVALUHS-S-2M
15290
Square Opal Diffuser



ORLRPVALUHS-S20-1M
15289
Square Opal Diffuser




ORLRPVALUHS-S1817-3M
15288
Square Opal Diffuser



ORLRPVALUHS-S17-2M
15287
Semi Recessed Opal Diffuser



ORLRPVALUHS-R-2M
15281
Round Opal Diffuser



ORLRPVALUHS-NB-2M
15271
Narrow Beam Diffuser



ORLRPVALUHS-CF-2M
15264
Coffe Profile



ORLRPVALUHS-C18-R-2M
15260
Corner Opal Diffuser