


Ref:

ORLBH16-2-WH-LED-3000K-MS


Item No: ORLBH – 39961

orlight[®]
FROM SOURCE TO SITE

High powered BH16-2 surface fixture, feature IP65 rated construction with a textured epoxy finish. The product includes integrated LED power supply with solid state chipset and polycarbonate diffuser for glare reduction. A CRI value of Ra > 80 ensures light quality. Available in Black, White and bespoke RAL finishes. Please Note: This product does not support hot plugging.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	10W
Lumen Output	978LM
Efficacy	98LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	110°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Milliamp / Current	250MA
Driver Configuration	INTEGRAL
Control	MICROWAVE SENSOR

CONSTRUCTION

Installation	SURFACE MOUNTED
Construction	ALUMINIUM
Diameter	275 MM
Width / Depth	74 MM
Weight	1.3KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temperature	-20°C - +45°C

EMERGENCY


Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

ORLBH16-2-WH-LED-3000K-MS


Item No: ORLBH – 39961

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



FIXING DETAILS



PLEASE NOTE:

This product does not support hot plugging