


Ref:

EZ2-231-27W-WH-3K-DALI


Item No: EZENTIAL – 18270

orlight[®]
FROM SOURCE TO SITE

Ezential-2-231 Solid State fixture combines advance thermal management with a 2835 SMD Samsung chipset to enable superior performance. Aluminium construction to IP54 with opal diffuser for glare reduction. A single chipset ensures uniformity of the light beam with a CRI>80 light quality assurance. Available in combination with 1-10V and DALI dimmable Power Supplies. Please Note: This product does not support hot plugging. Orlight does not recommend cutting of holes prior to receipt of product in hand.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	27W
Lumen Output	4050LM
Efficacy	150LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	115°
Chipset	SAMSUNG 2835 SMD
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	38-42V
Milliamp / Current	600MA
Driver Configuration	REMOTE
Control	DALI DIMMABLE

CONSTRUCTION

Installation	RECESSED
Construction	ALUMINIUM
Diameter	231 MM
Height	47.5 MM
Cutout	204 MM
Weight	0.98KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP54

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	REMOTE

EZ2-231-27W-WH-3K-DALI

Item No: EZENTIAL – 18270

LIGHT DISTRIBUTION

