

Ref:

SASI1430-16W-4K-9010-DALI-B-EM

Item No: SASI – 29043

orlight[®]
FROM SOURCE TO SITE

Utilises high intensity LED's to achieve up to 121 lumens per circuit Watt with a CRI>80 for light quality assurance. Matt white finished Aluminium surround with PMMA diffuser. Compliant with DALI or 0-10V protocols in conjunction with applicable drivers. 3 hour emergency version available. Please Note: This product does not support hot plugging.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	16W
Lumen Output	1936LM
Efficacy	121LM/W
CCT	4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	90°
Chipset	SAMSUNG L561B
Chip Life	L70 > 36,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	36V
Milliamp / Current	350MA
Driver Configuration	REMOTE
Control	DALI DIMMABLE

CONSTRUCTION

Installation	CEILING RECESSED
Construction	ALUMINIUM
Length	1394 MM
Width / Depth	297 MM
Height	30 MM
Diffuser	PMMA
Finish	WHITE
RAL	RAL 9010
IP Rating	IP20


EMERGENCY

Emergency	YES
Emergency Configuration	REMOTE
Emergency Duration	EMERGENCY 3HRS
EM Lumen	387LM

SASI1430-16W-4K-9010-DALI-B-EM

Item No: SASI – 29043

LIGHT DISTRIBUTION



SUSPENSION KIT



SUS-KIT-LOOP
17041
Suspension Kit Loop



SUS-KIT-PANEL-GP
17047
Suspension Kit Gripper