

Ref:

# LX4-7W-4000K


Item No: LX4 – 30013

**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

LX4 switched lamp has been designed to incorporate a 7W LED chipset in a smaller package. Advanced thermal management allows for greater power and performance. A CRI value > 82 provides light quality assurance and the single high power chipset ensures uniformity of beam.



## DIMENSIONS



## OPTICAL PERFORMANCE

|              |                 |
|--------------|-----------------|
| Wattage      | 7W              |
| Lumen Output | 1031LM          |
| Efficacy     | 147LM/W         |
| CCT          | 4000K           |
| CRI          | CRI > 82        |
| Binning      | 2 STEP MACADAMS |
| Beam Angle   | 60°             |
| Chipset      | ORLIGHT COB     |
| Chip Life    | L70 > 36,000HRS |

## ELECTRICAL

|                    |          |
|--------------------|----------|
| Voltage            | 220-240V |
| Milliamp / Current | 55MA     |
| Control            | SWITCHED |

## CONSTRUCTION

|                               |           |
|-------------------------------|-----------|
| Installation                  | RETROFIT  |
| Construction                  | ALUMINIUM |
| Diameter                      | 50 MM     |
| Height                        | 55 MM     |
| Weight                        | 0.025KG   |
| Finish                        | WHITE     |
| IP Rating                     | IP20      |
| Operating Ambient Temperature | -15-45°C  |
| Lamp Base                     | GU10      |

## LIGHT DISTRIBUTION

