

Ref:

LEO355-2-WH-LED-3000K-MS


Item No: LEO – 34218

orlight[®]
FROM SOURCE TO SITE

High output Architectural surface mounted fixture constructed from Aluminium base and Polycarbonate anti-glare diffuser, with CRI>80 to ensure light quality. Emergency options available.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	23W
Lumen Output	2944LM
Efficacy	128LM/W
CCT	3000K
CRI	CRI > 83
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Driver Configuration	INTEGRAL
Control	MICROWAVE SENSOR

CONSTRUCTION

Installation	SURFACE
Construction	ALUMINIUM
Diameter	355 MM
Width / Depth	100 MM
Weight	0.95KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
Operating Ambient Temperature	-40°C - +55°C


EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

LEO355-2-WH-LED-3000K-MS

Item No: LEO – 34218

LIGHT DISTRIBUTION



FIXING DETAILS

