

Ref:

# SM-WH-4K-2464-EM


Item No: ORLINE-50 – 25857

**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

Online Surface uses a tongue-and-groove locking mechanism for seamless connection between multiple lengths, with designs from isolated modules to continuous lines or custom shapes. Integral control gear, multiple power outputs, CRI>80. For configurations beyond a standard single length, refer to the length matrix for options up to 15M. For bespoke configurations (lengths beyond 15M, low UGR, wattage, colour temperature, tuneable white, corner, square, rectangular, cross or circular shapes), contact [sales@orlight.com](mailto:sales@orlight.com)



## DIMENSIONS



## OPTICAL PERFORMANCE

|                      |                  |
|----------------------|------------------|
| Wattage              | 64W              |
| Lumen Output         | 8000LM           |
| Efficacy             | 125LM/W          |
| CCT                  | 4000K            |
| CRI                  | CRI > 80         |
| Binning              | 2 STEP MACADAMS  |
| Beam Angle           | 120°             |
| Chipset              | ORLIGHT LED      |
| Calculated Chip Life | L70 > 105,000HRS |

## ELECTRICAL

|                             |                  |
|-----------------------------|------------------|
| Constant Current or Voltage | CONSTANT CURRENT |
| Voltage                     | 110-240V         |
| Milliamp / Current          | 300MA            |
| Driver Configuration        | INTEGRAL         |
| Control                     | SWITCHED         |

## CONSTRUCTION

|               |                 |
|---------------|-----------------|
| Installation  | SURFACE MOUNTED |
| Construction  | ALUMINIUM       |
| Length        | 2464 MM         |
| Width / Depth | 50 MM           |
| Height        | 90 MM           |
| Finish        | WHITE           |
| RAL           | RAL 9016        |
| IP Rating     | IP20            |


## EMERGENCY

|                         |                |
|-------------------------|----------------|
| Emergency               | YES            |
| Emergency Configuration | INTEGRAL       |
| Emergency Duration      | EMERGENCY 3HRS |
| EM Lumen                | 310LM          |

# SM-WH-4K-2464-EM

Item No: ORLINE-50 – 25857

## LIGHT DISTRIBUTION



## ADDITIONAL PRODUCT IMAGES



## ADDITIONAL DIMENSIONS

