

Ref:

LUNEX-600-20W-4K-DALI

Item No: LUNEX – 41671

orlight[®]
FROM SOURCE TO SITE

The LUNEX-600 is a premium 20W DALI 4K linear LED tubular light designed for commercial interiors and architectural lighting schemes. This model is supplied as a non-linkable fixture. Its sleek form and high-efficiency output deliver wide 120° illumination with excellent visual comfort. A PMMA diffuser and 316L stainless steel end caps offer a refined, modern aesthetic. Ideal for offices, clean zones, and exposed ceilings in contemporary environments. Supplied with a Quick-Fit surface bracket; suspension kit available separately.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	20W
Lumen Output	3120LM
Efficacy	156LM/W
CCT	4000K
CRI	CRI > 80
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 100,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Milliamp / Current	135MA
Driver Configuration	INTEGRAL
Control	DALI DIMMABLE

CONSTRUCTION

Installation	SURFACE / SUSPENDED
Construction	PMMA
Diameter	72MM
Length	600 MM
Weight	1KG
Finish	STAINLESS STEEL
IP Rating	IP66
IK Rating	IK06
Operating Ambient Temperature	-20°C - +40°C

EMERGENCY


Emergency	AVAILABLE
Emergency Configuration	REMOTE

LUNEX-600-20W-4K-DALI

Item No: LUNEX – 41671

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES



FIXING DETAILS



SUSPENSION KIT



999-ORLALP018-R-SW

13781

Suspension Kit