

Ref:

PUNCH-600-WH-4K-DALI-B-EM



Item No: PUNCH – 35066

orlight[®]
FROM SOURCE TO SITE

Vandal resistant linear surface fixture, expertly crafted from durable sheet steel. This fixture boasts an exceptional IK10++ impact resistance rating, ensuring unparalleled durability. With an IP65 rating, this fixture provides superior protection against dust and water, making it suitable for indoor and covered outdoor applications.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	16W
Lumen Output	2224LM
Efficacy	139LM/W
CCT	4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	220-240V
Milliamp / Current	400MA
Driver Configuration	INTEGRAL
Control	DALI DIMMABLE

CONSTRUCTION

Installation	SURFACE
Construction	SHEET STEEL
Length	628 MM
Width / Depth	160 MM
Height	78 MM
Finish	WHITE
RAL	RAL 9016
IP Rating	IP65
IK Rating	IK10++
Operating Ambient Temperature	-20°C - +40°C


EMERGENCY

Emergency	YES
Emergency Configuration	INTEGRAL
Emergency Duration	EMERGENCY 3HRS
EM Lumen	445LM

PUNCH-600-WH-4K-DALI-B-EM

Item No: PUNCH – 35066

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES

