

Ref:

MAC600-SUS-DUO-40W-WH-3K-4K-DALI


Item No: MAC SUSPENDED – 40827

orlight[®]
FROM SOURCE TO SITE

The MAC-600 Suspended DUO is made from durable Aluminium, available in White RAL9016 or Black RAL9005 finish, for suspended installation with a modern floating effect with both direct and indirect illumination. 2-Step MacAdams binning for precise colour consistency; CRI>80. UGR<19 for glare-free illumination, suited to offices, retail and hospitality. Supplied with an integral driver.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	40W
Lumen Output	4800LM / 5200LM
Efficacy	120LM/W / 130LM/W
CCT	3000K/4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	92°
UGR	UGR < 19
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	220-240V
Milliamp / Current	350MA
Driver Configuration	INTEGRAL
Control	DALI DIMMABLE
Cable Length	1500MM

CONSTRUCTION

Installation	SUSPENDED
Construction	ALUMINIUM
Diameter	600 MM
Height	76 MM
Weight	7.12KG
Diffuser	MICROPRISMATIC
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
IK Rating	IK03
Operating Ambient Temperature	-20°C - +45°C

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

MAC600-SUS-DUO-40W-WH-3K-4K-DALI

Item No: MAC SUSPENDED – 40827

orlight®
FROM SOURCE TO SITE

LIGHT DISTRIBUTION

