


Ref:

ORLLED600-IP65-35W-4K-9016


Item No: PANEL – 27303

orlight[®]
FROM SOURCE TO SITE

Solid State IP65 LED panel light 600x600, matt white finished Aluminium surrounded with TPA compliant V0 diffuser. Low energy solution for office and commercial applications. Offering benefits such as instant start, no flickering, silent running and no maintenance. Please Note: This product does not support hot plugging.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	35W
Lumen Output	4760LM
Efficacy	136LM/W
CCT	4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	32-36V
Milliamp / Current	900MA
Driver Configuration	REMOTE
Control	SWITCHED

CONSTRUCTION

Installation	CEILING RECESSED
Construction	ALUMINIUM
Length	595 MM
Width / Depth	595 MM
Height	8 MM
Weight	3.05KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP65


EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	REMOTE


ORLLED600-IP65-35W-4K-9016

Item No: PANEL – 27303

LIGHT DISTRIBUTION



SURFACE MOUNTING KIT



ORLLED600-SMK-9016
14812
Surface Mounting Kit for Led Panel