

Ref:

SUS-WH-3K-2044-EM

Item No: ORLINE-50 – 26325

orlight[®]
FROM SOURCE TO SITE

Online Suspended uses a tongue-and-groove locking mechanism for seamless connection between multiple lengths, with designs from isolated modules to continuous lines or custom shapes. Integral tridonic control gear, multiple power outputs, CRI>80. For configurations beyond a standard single length, refer to the length matrix for options up to 15M. For bespoke configurations (lengths beyond 15M, low UGR, wattage, colour temperature, tuneable white, corner, square, rectangular, cross or circular shapes), contact sales@orlight.com



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	53W
Lumen Output	6148LM
Efficacy	116LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	110-240V
Milliamp / Current	300MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	SUSPENDED
Construction	ALUMINIUM
Length	2044 MM
Width / Depth	50 MM
Height	90 MM
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20


EMERGENCY

Emergency	YES
Emergency Configuration	INTEGRAL
Emergency Duration	EMERGENCY 3HRS
EM Lumen	290LM


SUS-WH-3K-2044-EM

Item No: ORLINE-50 – 26325

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES



ADDITIONAL DIMENSIONS

