

Ref:

CL-RT4024-BL-4K-DALI


Item No: CROSSLINE – 10549

orlight[®]
FROM SOURCE TO SITE

Maxi Twin adjustable LED track mounted spot constructed from Aluminium and finished in Black RAL9005. This product offers a versatile range of motion with up to 90° tilt on the vertical axis and 360° rotation. Available in 3000K & 4000K colour temperature. CRI >90 for light quality assurance.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	24W
Lumen Output	1620LM
Efficacy	68LM/W
CCT	4000K
CRI	CRI > 90
Binning	2 STEP MACADAMS
Beam Angle	18°
Chipset	OSRAM LED
Chip Life	L70 > 50,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT VOLTAGE
Voltage	48V
Control	DALI DIMMABLE


CONSTRUCTION

Installation	TRACK
Construction	ALUMINIUM
Diameter	40 MM X 2
Length	105 MM
Tilt	90°
Rotation	360°
Finish	BLACK
RAL	RAL 9005
IP Rating	IP20

CL-RT4024-BL-4K-DALI

Item No: CROSSLINE – 10549


LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES



STANDARD DALI TRACK



CL-ST-BL-2M-DALI
10556
Standard DALI Track

SLIM DALI TRACK



CL-SLT-BL-2M-DALI
10552
Slim DALI Track

CL-RT4024-BL-4K-DALI

Item No: CROSSLINE – 10549

orlight[®]
FROM SOURCE TO SITE


RECESSED/TRIMLESS DALI TRACK



CL-RCT-BL-2M-DALI

10527

Recessed/Trimless DALI Track



CL-RCT-BL-3M-DALI

10528

Recessed/Trimless DALI Track