

Ref:

VANTA-170-30W-BL-3K-EM

Item No: VANTA – 45942


orlight[®]
FROM SOURCE TO SITE

The VANTA-170 is a high-performance IP65 external downlight for efficient, low-glare outdoor lighting, with a deep reflector and tempered glass cover for architectural performance. IP rated top and bottom, protected against dust and water ingress; driver located remotely for flexible installation in commercial, residential and architectural exterior projects. Available as a Switched-EM option; suits entrances, walkways, canopies, facades and covered outdoor spaces. Note: Does not support hot plugging; do not cut holes before receiving product.



NEW!

DIMENSIONS



OPTICAL PERFORMANCE

Wattage	30W
Lumen Output	3060LM
Efficacy	102LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	60°
Chipset	BRIDGELUX
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	220-240V
Milliamp / Current	750MA
Driver Configuration	REMOTE
Control	SWITCHED

CONSTRUCTION

Installation	CEILING RECESSED
Construction	ALUMINIUM
Diameter	172 MM
Height	69 MM
Cutout	150 MM
Tilt	FIXED
Finish	BLACK
RAL	RAL 9005
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temperature	-20°C - +45°C

EMERGENCY


Emergency	YES
Emergency Configuration	REMOTE
Emergency Duration	EMERGENCY 3HRS
EM Lumen	306LM

VANTA-170-30W-BL-3K-EM

Item No: VANTA – 45942

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



PLEASE NOTE:

- This product does not support hot plugging
- Do not cut holes before receiving product.