


Ref:

CL-RS253-BL-3K-DALI


Item No: CROSSLINE – 10536

orlight[®]
FROM SOURCE TO SITE

Adjustable LED track mounted mini spot constructed from Aluminium and finished in Black RAL9005. This product offers a versatile range of motion with up to 90° tilt on the vertical axis and 360° rotation. Available in 3000K colour temperature. CRI >90 for light quality assurance.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	3W
Lumen Output	195LM
Efficacy	65LM/W
CCT	3000K
CRI	CRI > 90
Binning	2 STEP MACADAMS
Beam Angle	18°
Chipset	OSRAM LED
Chip Life	L70 > 50,000HRS


ELECTRICAL

Constant Current or Voltage	CONSTANT VOLTAGE
Voltage	48V
Control	DALI DIMMABLE

CONSTRUCTION

Installation	TRACK
Construction	ALUMINIUM
Diameter	25 MM
Length	42 MM
Tilt	90°
Rotation	360°
Finish	BLACK
RAL	RAL 9005
IP Rating	IP20

LIGHT DISTRIBUTION



CL-RS253-BL-3K-DALI


Item No: CROSSLINE – 10536

orlight[®]
FROM SOURCE TO SITE

ADDITIONAL PRODUCT IMAGES



STANDARD DALI TRACK



CL-ST-BL-2M-DALI

10556

Standard DALI Track

SLIM DALI TRACK




CL-SLT-BL-2M-DALI

10552

Slim DALI Track

RECESSED/TRIMLESS DALI TRACK



CL-RCT-BL-2M-DALI

10527

Recessed/Trimless DALI Track



CL-RCT-BL-3M-DALI

10528

Recessed/Trimless DALI Track