

Ref:

LUNEX-PRO-600-20W-4K-EM

Item No: LUNEX PRO – 41694

orlight[®]
FROM SOURCE TO SITE

The LUNEX PRO-600 is a robust 20W 4K EM tri-proof LED luminaire for demanding environments including car parks, transport hubs and public infrastructure, supplied as a linkable fixture. Rated IP66 and IK10, delivers durable, reliable performance with wide 120° illumination. Tough polycarbonate diffuser and 316L stainless steel end caps for strength and corrosion resistance. Supplied with a Quick-Fit surface mounting bracket as standard; suspension kit available separately. Please Note: The Lunex Pro-600-EM requires remote emergency gear.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	20W
Lumen Output	2800LM
Efficacy	140LM/W
CCT	4000K
CRI	CRI > 80
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 100,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Milliamp / Current	135MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	SURFACE / SUSPENDED
Construction	POLYCARBONATE
Diameter	72MM
Length	600 MM
Finish	STAINLESS STEEL
IP Rating	IP66
IK Rating	IK10
Operating Ambient Temperature	-20°C - +40°C

EMERGENCY


Emergency	YES
Emergency Configuration	REMOTE
Emergency Duration	EMERGENCY 3HRS
EM Lumen	420LM

LUNEX-PRO-600-20W-4K-EM

Item No: LUNEX PRO – 41694

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES



SUSPENSION KIT



999-ORLALP018-R-SW

13781

Suspension Kit