

Ref:

MAC900-SUS-DUO-60W-WH-3K-4K


Item No: MAC SUSPENDED – 40865

orlight[®]
FROM SOURCE TO SITE

The MAC-900 Suspended DUO is made from durable Aluminium, available in White RAL9016 or Black RAL9005 finish, for suspended installation with a modern floating effect with both direct and indirect illumination. 2-Step MacAdams binning for precise colour consistency; CRI>80. UGR<19 for glare-free illumination, suited to offices, retail and hospitality. Supplied with an integral driver.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	60W
Lumen Output	7200LM / 7800LM
Efficacy	120LM/W / 130LM/W
CCT	3000K/4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	92°
UGR	UGR < 19
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	220-240V
Milliamp / Current	350MA
Driver Configuration	INTEGRAL
Control	SWITCHED
Cable Length	1500MM

CONSTRUCTION

Installation	SUSPENDED
Construction	ALUMINIUM
Diameter	900 MM
Height	76 MM
Weight	12.58KG
Diffuser	MICROPRISMATIC
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
IK Rating	IK03
Operating Ambient Temperature	-20°C - +45°C

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

MAC900-SUS-DUO-60W-WH-3K-4K

Item No: MAC SUSPENDED – 40865

orlight®
FROM SOURCE TO SITE

LIGHT DISTRIBUTION

