

Ref:

APOLLO-SF-15W-BL-3000K


Item No: APOLLO – 27958

orlight[®]
FROM SOURCE TO SITE

Surface mounted Luminaire combining slim cylinder housing design with integral LED driver. Versatile range of motion to 90° on the vertical axis and 355° rotation allowing for direction of light to application. A single chipset ensures uniformity of the light beam with interchangeable optics to 24° as standard and 18° and 36° and order only accessories. CRI >90 for light quality assurance, consistency is adhered to with a 2-Step MacAdams Ellipse binning strategy.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	15W
Lumen Output	1485LM
Efficacy	99LM/W
CCT	3000K
CRI	CRI > 92
Binning	2 STEP MACADAMS
Beam Angle	24°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Voltage	220-240V
Milliamp / Current	0.12AmA
Driver Configuration	INTEGRAL
Control	MAINS TRAILING EDGE

CONSTRUCTION

Installation	SURFACE MOUNTED
Construction	ALUMINIUM
Diameter	55 MM
Length	150 MM
Tilt	90°
Rotation	355°
Finish	BLACK
RAL	RAL 9005
IP Rating	IP20


EMERGENCY

Emergency Configuration	REMOTE
-------------------------	--------

APOLLO-SF-15W-BL-3000K

Item No: APOLLO – 27958

LIGHT DISTRIBUTION



ACCESSORIES



APOLLO-18DEG-LENS
10338
18 Degree Lens for Apollo Track light



APOLLO-24DEG-LENS
10341
24 Degree Lens for Apollo Track light



APOLLO-36DEG-LENS
10342
36 Degree Lens for Apollo Track light



APOLLO-HC-MESH
10343
Honeycomb Mesh for Atlas