

Ref:

CUBIC1515H-9016-UD-4K-DALI

Item No: CUBIC – 17479

orlight[®]
FROM SOURCE TO SITE

The CUBIC is a suspended linear light constructed from Aluminium and rated to IP20. Colour consistency is adhered to with a 2-Step MacAdams Ellipse binning strategy alongside an LED chipset at CRI>80 ensuring light quality. The fitting also features an integral Samsung driver. The suspension cables can be adjusted to a minimum of 350mm and maximum 1800mm in length. Available as Switched, 1-10V and DALI dimming options in 4000K colour temperature.



UGR
< 19

IP20

DIMENSIONS



OPTICAL PERFORMANCE

Wattage	45W
Lumen Output	5130LM
Efficacy	114LM/W
CCT	4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	92°
UGR	UGR < 19
Chipset	SAMSUNG LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	220V
Driver Configuration	INTEGRAL
Control	DALI DIMMABLE

CONSTRUCTION

Installation	SUSPENDED
Construction	ALUMINIUM
Length	1500 MM
Width / Depth	150 MM
Height	52 MM
Diffuser	MICROPRISMATIC
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
Operating Ambient Temperature	-20°C - +35°C

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

CUBIC1515H-9016-UD-4K-DALI

Item No: CUBIC – 17479

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION

