

Ref:

DUOWM-WH-3K-1834-EM


Item No: ORLINE-50 – 23619

orlight[®]
FROM SOURCE TO SITE

Online Wall Mounted Duo uses a tongue-and-groove locking mechanism for seamless connection between multiple lengths, with designs from isolated modules to continuous lines or custom shapes. Integral tridronic control gear, multiple power outputs, CRI>80. For configurations beyond a standard single length, refer to the length matrix for options up to 15M. For bespoke configurations (lengths beyond 15M, low UGR, wattage, colour temperature, tuneable white, corner, square, rectangular, cross or circular shapes), contact sales@orlight.com



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	39W
Lumen Output	5460LM
Efficacy	140LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	110-240V
Milliamp / Current	200MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	WALL MOUNTED
Construction	ALUMINIUM
Length	1834 MM
Width / Depth	50 MM
Height	90 MM
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20


EMERGENCY

Emergency	YES
Emergency Configuration	INTEGRAL
Emergency Duration	EMERGENCY 3HRS
EM Lumen	360LM

DUOWM-WH-3K-1834-EM

Item No: ORLINE-50 – 23619

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES

