

Ref:

ORLTE6024EVO4-2700K-IP65-10W-S

Item No: EVO4 – 15465-S



High output self-adhesive LED strip. The EVO4 strip is supplied per metre complete with plug and play connections. Featuring 3M adhesive backing for simple installation. It can be cut every 33mm, allowing you to tailor the strip to your exact needs. A layer of Nano coating provides an IP65 rating. CRI>90 standard ensures enhanced light quality with uncompromising standards.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	10W/M
Lumen Output	1290LM
Efficacy	129LM/W
CCT	2700K
CRI	CRI > 92
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	SMD 2835
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT VOLTAGE
Voltage	24V
Cable Length	300 MM

CONSTRUCTION


Installation	PLUG & PLAY
Construction	PCB & NANO COATING
Width / Depth	12 MM
Height	2 MM
IP Rating	IP65
Cut Points	33 MM
Max Cut Length	10000 MM

ORLTE6024EVO4-2700K-IP65-10W-S

Item No: EVO4 – 15465-S

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



DRIVER CONFIGURATION

CONTROL	DRIVER	CODE	MAX. LENGTH
Switched	ORLRPV2435	15210	3M
Switched	ORLRPV2460	15214	6M
Switched	ORLRPV24100	15199	10M
Mains Dimmable	ORLRPV25-24MD	15221	2M
Mains Dimmable	ORLRPV50-24MD	15250	5M
Mains Dimmable	ORLRPV100-24MD	15169	10M
1-10V Interface	ORLRPV-INTERFACE-MINI	15357	10M
DALI	ORLDALIINTERFACE-12-24-36V	14054	10M

POWER SUPPLY



ORLRPV2460
15214
24V Switched Driver



ORLRPV2435
15210
24V Switched Driver



ORLRPV24100
15199
24V Switched Driver

MAINS DIMMABLE DRIVER



ORLRPV50-24MD
15250
24V Mains Dimmable Driver



ORLRPV25-24MD
15221
24V Mains Dimmable Driver



ORLRPV100-24MD
15169
24V Mains Dimmable Driver

ORLTE6024EVO4-2700K-IP65-10W-S

Item No: EVO4 – 15465-S

orlight[®]
FROM SOURCE TO SITE

1-10V/DALI INTERFACE



ORLRPV-INTERFACE-MINI

15357

Constant Voltage Interface for 1-10V dimming


COMPATIBLE DIFFUSER



ORLDALIINTERFACE-12-24-36V

14054


DALI/PUSH Dimmable Interface



ORLRPVHSEVOPL2-S-CL-2M

15348


Square Clear Diffuser



ORLRPVHSEVOPL2C-S-2M

15338

Square Corner Opal Diffuser



ORLRPVHSEVOPL2C-R-2M

15334

Round Corner Opal Diffuser



ORLRPVALUHS-TP7-2M

15322


Narrow Opal Diffuser



ORLRPVALUHS-TP30-2M

15319


Square Top Lit Opal Diffuser



ORLRPVALUHS-TL-2M

15309

Trimless Opal Diffuser



ORLRPVALUHS-TL15-2M

15307


Trimless Opal Diffuser



ORLRPVALUHS-SR-WH-2M

15304

Semi Recessed Opal Diffuser



ORLRPVALUHS-SR-AL-2M

15299


Semi Recessed Opal Diffuser



ORLRPVALUHS-S-2M

15290

Square Opal Diffuser



ORLRPVALUHS-S20-1M


15289

Square Opal Diffuser


ORLTE6024EVO4-2700K-IP65-10W-S

Item No: EVO4 – 15465-S

orlight[®]
FROM SOURCE TO SITE



ORLRPVALUHS-S1817-3M
15288
Square Opal Diffuser



ORLRPVALUHS-S17-2M
15287
Semi Recessed Opal Diffuser



ORLRPVALUHS-R-2M
15281
Round Opal Diffuser



ORLRPVALUHS-NB-2M
15271
Narrow Beam Diffuser



ORLRPVALUHS-CF-2M
15264
Coffe Profile



ORLRPVALUHS-C18-R-2M
15260
Corner Opal Diffuser