

Ref:

LUNEX-600-20W-3K-EM

Item No: LUNEX – 41666

orlight[®]
FROM SOURCE TO SITE

The LUNEX-600 is a premium 20W EM 3K linear LED tubular light for commercial interiors and architectural lighting schemes, supplied as a non-linkable fixture. Sleek form and high-efficiency output deliver wide 120° illumination with excellent visual comfort. PMMA diffuser and 316L stainless steel end caps for a refined, modern look. Suited to offices, clean zones and exposed ceilings. Supplied with a Quick-Fit surface bracket; suspension kit available separately. Please Note: The Lunex-600-EM requires remote emergency gear.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	20W
Lumen Output	2660LM
Efficacy	133LM/W
CCT	3000K
CRI	CRI > 80
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 100,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Milliamp / Current	135MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	SURFACE / SUSPENDED
Construction	PMMA
Diameter	72MM
Length	600 MM
Finish	STAINLESS STEEL
IP Rating	IP66
IK Rating	IK06
Operating Ambient Temperature	-20°C - +40°C

EMERGENCY


Emergency	YES
Emergency Configuration	REMOTE
Emergency Duration	EMERGENCY 3HRS
EM Lumen	399LM

LUNEX-600-20W-3K-EM

Item No: LUNEX – 41666

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES



FIXING DETAILS



SUSPENSION KIT



999-ORLALP018-R-SW

13781

Suspension Kit