

Ref:

CASCADE-340-AL-3000K


Item No: CASCADE – 10419

orlight[®]
FROM SOURCE TO SITE

Recessed in-ground fixture, Aluminium construction, IP67 rated; CREE chipset with narrow beam for wall wash. Mechanical tilt mechanism angles the light source through 0°, 3°, 5° or 8°. CRI >80 with 2-Step MacAdams Ellipse colour consistency. Micro louvre minimises glare; projection range up to 10M for even illumination of large structures. Integrated DALI control option. For alternative colour temperatures contact sales; this product does not support hot plugging.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	15W
Lumen Output	1000LM
Efficacy	67LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	20°
Chipset	CREE XBD
Chip Life	L70 > 60,500HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	100-240V
Driver Configuration	INTEGRAL
Control	SWITCHED
Cable Length	420MM

CONSTRUCTION


Installation	RECESSED
Construction	ANODIZED ALUMINIUM
Length	340 MM
Width / Depth	65 MM
Height	92 MM
Tilt	0° / 3° / 5° / 8°
Finish	ANODIZED ALUMINIUM
IP Rating	IP68
IK Rating	IK10
Operating Ambient Temperature	-20°C - +40°C

CASCADE-340-AL-3000K

Item No: CASCADE – 10419

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



PLEASE NOTE:

- For alternative colour temperatures contact sales
- This product does not support hot plugging

ACCESSORIES



CASCADE-340-TROUGH

10421

Trough for CASCADE Range