

Ref:

BAYTRON-300-100W-3K




Item No: BAYTRON – 41593

orlight[®]
FROM SOURCE TO SITE

A compact, high-efficiency luminaire delivering up to 140lm/W, ideal for smaller-scale industrial and commercial spaces. Available in 100W with 3000K CCT, it features a standard 90° beam angle with optional optics, flexible suspension or surface mounting, and robust IP65/IPK10 protection with Ra>80 colour rendering.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	100W
Lumen Output	14000LM
Efficacy	140LM/W
CCT	3000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	90°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Driver Configuration	FIXTURE MOUNTED
Control	SWITCHED

CONSTRUCTION

Installation	SUSPENDED
Construction	ALUMINIUM
Length	313 MM
Width / Depth	130 MM
Height	108 MM
Weight	2.3KG
Finish	SILVER
IP Rating	IP65
IK Rating	IK10
Operating Ambient Temperature	-35°C - +50°C

EMERGENCY


Emergency	AVAILABLE
Emergency Configuration	FIXTURE MOUNTED

BAYTRON-300-100W-3K

Item No: BAYTRON – 41593

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



ADDITIONAL PRODUCT IMAGES

