

Ref:

# VANTA-170-18W-BL-3K

Item No: VANTA – 45907


**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

The VANTA-170 is a high-performance IP65 external downlight for efficient, low-glare outdoor lighting, with a deep reflector and tempered glass cover for architectural performance. IP rated top and bottom, protected against dust and water ingress; driver located remotely for flexible installation in commercial, residential and architectural exterior projects. Available as a Switched option; suits entrances, walkways, canopies, facades and covered outdoor spaces. Note: Does not support hot plugging; do not cut holes before receiving product.



**NEW!**

## DIMENSIONS



## OPTICAL PERFORMANCE

|                      |                  |
|----------------------|------------------|
| Wattage              | 18W              |
| Lumen Output         | 1836LM           |
| Efficacy             | 102LM/W          |
| CCT                  | 3000K            |
| CRI                  | CRI > 80         |
| Binning              | 2 STEP MACADAMS  |
| Beam Angle           | 60°              |
| Chipset              | BRIDGELUX        |
| Calculated Chip Life | L70 > 105,000HRS |

## ELECTRICAL

|                             |                  |
|-----------------------------|------------------|
| Constant Current or Voltage | CONSTANT CURRENT |
| Voltage                     | 220-240V         |
| Milliamp / Current          | 450MA            |
| Driver Configuration        | REMOTE           |
| Control                     | SWITCHED         |

## CONSTRUCTION

|                               |                  |
|-------------------------------|------------------|
| Installation                  | CEILING RECESSED |
| Construction                  | ALUMINIUM        |
| Diameter                      | 172 MM           |
| Height                        | 69 MM            |
| Cutout                        | 150 MM           |
| Tilt                          | FIXED            |
| Finish                        | BLACK            |
| RAL                           | RAL 9005         |
| IP Rating                     | IP65             |
| IK Rating                     | IK08             |
| Operating Ambient Temperature | -20°C - +45°C    |

## EMERGENCY

|                         |           |
|-------------------------|-----------|
| Emergency               | AVAILABLE |
| Emergency Configuration | REMOTE    |


# VANTA-170-18W-BL-3K

Item No: VANTA – 45907

**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

## LIGHT DISTRIBUTION

---



## PLEASE NOTE:

---

- This product does not support hot plugging
- Do not cut holes before receiving product.