

Ref:

AXIAL-90-BL-10W-4K

Item No: AXIAL IP65 – 32560

orlight[®]
FROM SOURCE TO SITE


External IP65 solid-state surface mounted downlight, meticulously engineered to meet the highest standards of performance and durability. Its sleek black matte finish adds a touch of elegance to any space, including an integral driver. For added convenience, this downlight can be easily mounted using a BESA box. Additionally, we offer an IP20 variant for indoor applications, allowing for a cohesive lighting solution across various applications.



UGR
< 19

IP65

DIMENSIONS



OPTICAL PERFORMANCE

Wattage	10W
Lumen Output	1018LM
Efficacy	102LM/W
CCT	4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	36°
UGR	UGR < 19
Chipset	CITIZEN LED CHIPSET
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	200-240V
Milliamp / Current	200MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	CEILING MOUNTED
Construction	ALUMINIUM
Diameter	90 MM
Height	107 MM
Weight	0.7KG
Tilt	FIXED
Finish	BLACK
RAL	RAL 9005
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temperature	-20°C - +40°C

EMERGENCY


Emergency	AVAILABLE
-----------	-----------

AXIAL-90-BL-10W-4K

Item No: AXIAL IP65 – 32560

orlight[®]
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



FIXING DETAILS

