

Ref:

LEO355-2-WH-LED-4000K-MS-EM


Item No: LEO – 33944

orlight[®]
FROM SOURCE TO SITE

High output Architectural surface mounted fixture constructed from Aluminium base and Polycarbonate anti-glare diffuser, with CRI>80 to ensure light quality.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	23W
Lumen Output	3197LM
Efficacy	139LM/W
CCT	4000K
CRI	CRI > 83
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	ORLIGHT LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Driver Configuration	INTEGRAL
Control	MICROWAVE SENSOR-EM

CONSTRUCTION

Installation	SURFACE
Construction	ALUMINIUM
Diameter	355 MM
Width / Depth	100 MM
Weight	1.95KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
Operating Ambient Temperature	-40°C - +55°C


EMERGENCY

Emergency	YES
Emergency Configuration	INTEGRAL
Emergency Duration	EMERGENCY 3HRS
EM Lumen	385LM

LEO355-2-WH-LED-4000K-MS-EM

Item No: LEO – 33944

LIGHT DISTRIBUTION



FIXING DETAILS

